

## Glycerine 99,5% - Technical grade

### Characteristic & Quality specification

	Unit	Value	Analyse Method
Glycerol content	%	Min. 99,5	Ph. Eur. 2005 – 2.2.5.
Colour	APHA	Max. 100	ISO 2211
Ash Sulphate	%	Max. 0,1	Ph. Eur. 2005 – 2.4.14.
Water content	%	Max. 0,5	Ph. Eur. 2005 – 496, 2.5.12
Refractive index 20°C	n D 20	1.470-1.475	Ph. Eur. 2005 – 496, 2.2.6
Density 20°C	g/ml	Min. 1,260	Ph. Eur. 2005 – 496, 2.2.5

Glycerine technical is glycerol (1,2,3 – propanetriol), which is produced by distillation of crude glycerine, respectively further adjustment of the distillate. Technical glycerine is produced from raw materials of plant or animal origin.

### Form of supply

---

- Road tankers

### Storage

---

- The product should be stored in the original packing in dry, covered, clean warehouses, protected from the weather, with temperatures ranging from +10 to + 30 °C. Under these conditions the shelf life is 12 months from the date of production.

### Safety data

---

- This product is not classified as hazardous. For more information on the safety and handling, please refer to the corresponding MSDS.

Product data sheet is for information purposes only! Binding product's specification is defined in sales conditions or sales contract!

**Zeppoil Schwarzheide GmbH**  
Naundorfer Straße 40  
01987 Schwarzheide, Germany

